

Kima GG10


Application:

Thin floor construction in wet and dry areas.

Ordinary concrete constructions in wet and dry rooms.

Specification:

- Flameretardent, twin conductor with no electromagnetic fields.
- Steel armoured metallic sheath with minimum electric fields.
- Insulation class I
- IP67
- Operating temperature max +70°C.
- Mechanical strength, armoured class C according to EN60800.
- Voltage 230 Volt.
- Wattage 10 W/m.
- 2 m coldtail with metallic sheath.
- Manufactured according to EN60800, SS4242411.
- Complies with RoHS directive 2002/95/EC.



- 100 W/m² = c/c 10 cm
- 75 W/m² = c/c 13,5 cm
- 67 W/m² = c/c 15 cm
- 50 W/m² = c/c 20 cm
- 40 W/m² = c/c 25 cm

| Part no. | EAN no. | Product Type | Length (m) | Wattage (W) | Tolerance total (Ohm) |
|-------------|---------------|--------------|------------|-------------|-----------------------|
| E 89 877 01 | 7331002902348 | KIMA GG10 | 13 | 130 | 387 - 448 |
| E 89 877 02 | 7331002902355 | KIMA GG10 | 22 | 220 | 228 - 265 |
| E 89 877 03 | 7331002902362 | KIMA GG10 | 30 | 300 | 168 - 194 |
| E 89 877 04 | 7331002902379 | KIMA GG10 | 43 | 430 | 117 - 135 |
| E 89 877 05 | 7331002902386 | KIMA GG10 | 52 | 520 | 97 - 112 |
| E 89 877 06 | 7331002902393 | KIMA GG10 | 63 | 630 | 80 - 92 |
| E 89 877 07 | 7331002902409 | KIMA GG10 | 70 | 700 | 72 - 83 |
| E 89 877 08 | 7331002902416 | KIMA GG10 | 80 | 800 | 63 - 73 |
| E 89 877 09 | 7331002902423 | KIMA GG10 | 91 | 910 | 55 - 64 |
| E 89 877 10 | 7331002902430 | KIMA GG10 | 100 | 1000 | 50 - 58 |
| E 89 877 12 | 7331002902447 | KIMA GG10 | 117 | 1170 | 43 - 50 |
| E 89 877 13 | 7331002902607 | KIMA GG10 | 130 | 1300 | 39 - 45 |
| E 89 877 14 | 7331002902454 | KIMA GG10 | 142 | 1420 | 35 - 41 |
| E 89 877 16 | 7331002902614 | KIMA GG10 | 160 | 1600 | 31 - 36 |
| E 89 877 18 | 7331002902461 | KIMA GG10 | 182 | 1820 | 28 - 32 |